



| Size | Lug spacing a (mm) | Length L (mm) | Internal neck diameter $\varnothing d$ (mm) | Materials | Standard  | Weight (kg) | ID-No.        |
|------|--------------------|---------------|---|-----------|-----------|-------------|---------------|
| 25=D | 31                 | 55            | 18  | Al-forged | DIN 14301 | 0,09        | <b>131050</b> |
| 25=D | 31                 | 55            | 18  | Ms        |           | 0,28        | <b>131051</b> |
| 25=D | 31                 | 55            | 18  | Steel     |           | 0,25        | <b>131052</b> |
| 25=D | 31                 | 55            | 18  | Al-forged |           | 0,09        | <b>131053</b> |
| 25=D | 31                 | 55            | 18  | Al-forged | PN 40     | 0,09        | <b>131054</b> |
| 25=D | 31                 | 55            | 18  | Al-casted |           | 0,09        | <b>131055</b> |
| 52=C | 66                 | 55            | 36  | Al-forged |           | 0,34        | <b>131041</b> |
| 52=C | 66                 | 55            | 36  | Ms        |           | 0,4         | <b>131042</b> |
| 52=C | 66                 | 55            | 45  | Al-casted |           | 0,33        | <b>131002</b> |
| 52=C | 66                 | 55            | 45  | Al-forged | DIN 14302 | 0,32        | <b>131043</b> |
| 52=C | 66                 | 55            | 45  | Ms        | DIN 86202 | 0,4         | <b>131045</b> |
| 52=C | 66                 | 55            | 45  | Steel     |           | 0,35        | <b>131046</b> |
| 75=B | 89                 | 60            | 65  | Al-forged | DIN 14303 | 0,56        | <b>131047</b> |
| 75=B | 89                 | 60            | 65  | Ms        | DIN 86203 | 0,7         | <b>131005</b> |
| 75=B | 89                 | 60            | 65  | Steel     |           | 0,6         | <b>131048</b> |
| 75=B | 89                 | 60            | 65  | Steel     |           | 0,6         | <b>131049</b> |